

ILT490

Profiling Belt Radiometer

The NEW ILT490 incorporates the measurement capabilities and exceptional performance criteria of the original IL390 and IL290 UV Curing Light Bug with the improved features of the ILT400 including profiling, graphing, cost reduction, rechargeable batteries and A400 charger.

The ILT490 works with many lamp options from Iron doped, H and D type lamps, and standard UV sources.

The ILT490 Belt Radiometer, comes in two versions: the ILT490 broadband UV for 250-400 nm, and the ILT490C UVC for 205-345 nm (see graph below). Special "O" software is available for low light level applications for 1 mW/cm² to 2.5 W/cm² with profiling at 10 mW/cm² available at no additional cost.

SPECIFICATIONS

Dose Range: 5 mJ – 20 J/cm²

Temperature Range: 10° – 50° C (case temperature)

Irradiance Range: 10 mW/cm² – 20 W/cm²

Accuracy: Typically better than 6%

Cosine Receptor: Integrating sphere

Display: 4 significant digits


Display Graphics: Resolves 5% of full scale (peak irradiance)

Size: 12.7 x 111 x 161 mm (0.5" x 4.4" x 6.3")

FEATURES & BENEFITS

- ◇ NIST-traceable calibration
- ◇ Measurement spectrum matches industry standard IL390 (ILT490) & IL290 (ILT490C)
- ◇ Built-in re-chargeable batteries (includes A400 charger)
- ◇ Integrated exposure (J/cm²)
- ◇ Peak Irradiance (W/cm²)
- ◇ Intensity profiling with auto-scale
- ◇ Baseline profile memory
- ◇ Current - Baseline % Difference

SPECTRAL CURVES



InternationalLight
TECHNOLOGIES

NIST-Traceable Light Measurement Systems

10 Technology Drive
Peabody, MA 01960

Phone: (978) 818-6180 Fax: (978) 818-6181

Web: www.intl-lighttech.com