


## Torque Magnetometer (Tq-Mag)

DynaCool (D550) / PPMS (P550) / VersaLab (V550)



The torque magnetometer (Tq-Mag) measures the torque ( $\tau = \mathbf{m} \times \mathbf{B}$ ) exerted on a magnetic sample with moment,  $\mathbf{m}$ , by an applied field,  $\mathbf{B}$ . By definition, a torque is only present if a component of  $\mathbf{m}$  is orthogonal to  $\mathbf{B}$ . Therefore, torque magnetometry is a powerful tool in the study of small anisotropic single crystals and thin films. The torsion is measured using piezoresistive elements on a calibrated cantilever chip as a function of magnetic field, temperature, or angular orientation. The automated calibration procedure substantially minimizes offsets from gravity and temperature to the measured torque.

### Key Features

- Piezoresistive elements comprising a Wheatstone bridge are fabricated directly on the cantilever chip
- Integrated calibration loop on the cantilever chip
- Sample mounting entails only a small amount of vacuum grease to hold the sample to the cantilever with no additional wiring required
- Two chip variants are available:
  - (i) High-sensitivity chip for low noise ( $1 \cdot 10^{-9}$  N·m)
  - (ii) Large-moment chip which extends the upper range of the measurement to  $1 \cdot 10^{-4}$  N·m



Tq-Mag chip



Torque curves measured at room temperature of a 100 nm thick Fe film as a function of the angle of the applied field (with respect to the film normal). At high fields the curves reflect the uniaxial anisotropy of the sample.

### Torque Magnetometer Specifications

#### Torque [ $\tau$ ]

Noise Floor:	$1 \cdot 10^{-9}$ N·m (high sensitivity chip) $2 \cdot 10^{-8}$ N·m (large moment chip)
Maximum Torque:	$1 \cdot 10^{-5}$ N·m (high sensitivity chip) $1 \cdot 10^{-4}$ N·m (large moment chip)

#### Physical Parameters

Chip Size:	6 mm × 6 mm × 1 mm
Available Sample Volume:	1.5 mm × 1.5 mm × 1.5 mm
Maximum Sample Weight:	10 mg

**Operational Range** 1.8 to 400 K; 0 to 16 T

\*Stated value is for a 40 second sampling time  
Specifications are subject to change without notice.